

APOLLO

SPRAYERS

MANUAL

BAMBI AIR LTD

**152 Thimble Mill Lane
Heartlands
Birmingham
B7 5HT
United Kingdom
Tel: 44 (0) 121 322 2299
Fax: 44 (0) 121 322 2297**

**Email: sales@bambi-air.co.uk
www.bambi-air.co.uk**

ISSUE 6

INTRODUCTION

Your Apollo Sprayer is a precision engineered high quality product that will give years of reliable service and excellent results, provided you follow the instruction and advice given in this booklet.

See the back page for technical support.

CONTENTS

	Page
Safety Notes	2
Using the Hobby Plus Spray Gun	3 to 4
Using the ANB300 Spray Gun	5 to 8
Paint Viscosity	9
Basic Spraying Techniques	9 to 10
Filter Removal / Replacement	11
Fault Finding / Preventative Maintenance	12

SETTING UP

The Apollo spray system consists of three main items: the turbine unit, the spray gun and the hose.

Your first step is to connect the hose to the spray gun and the turbine. Some models have a push on fitting others have a quick connect fitting. Whichever hose you have do not use excessive force, see page 6.

When the turbine is running the Hobby Plus spray gun will exhaust air all the time.

The ANB300 spray gun will only exhaust air when you pull the trigger.

IMPORTANT

Read these safety instructions in conjunction with your Apollo manual

FOREWORD

Parts and service advice are available from your Apollo distributor.

It is important to quote the MODEL TYPE and SERIAL NUMBER in all communications.

The substitution of parts not manufactured or approved by Bambi Air Ltd, can impair the performance, service life and create potential mechanical or personal hazards as well as invalidating your warranty.

Operation and routine service are covered in this manual. Bambi Air Ltd, reserve the right to modify the contents of this manual without prior notice and the information given is in no way binding to the company.

SAFETY PRECAUTIONS

All spray painting can be a hazard to health and safety if not handled correctly.

- ! Never direct paint or any other fluids at any part of the human body
- ! Do not dismantle the spray gun or disconnect hoses until the turbine is switched off
- ! Site the turbine in a well ventilated area and position away from the user to ensure no solvent vapours can be drawn into the turbine. Particular attention must be paid when working indoors to ensure a sufficient flow of air will extract all solvent vapours. When working outside take into account the wind direction.
- ! Whenever spraying you must wear an appropriate face mask or respiratory equipment
- ! Always follow the material manufacturers application guidelines which can normally be found on the original container
- ! During operation the turbine outlet and hose connection will become quite hot to the touch, this is a normal operating condition, but care must be taken to prevent burns (when the turbine has been switched off allow sufficient time for the fitting to cool before attempting removal)

ELECTRICAL CONNECTIONS

! IMPORTANT !

Do not attempt any work on the turbine until it has been isolated from the mains electricity supply.


Turbines are supplied with a length of mains cable wires coded to IEC227 and IEC245.

i.e.. BLUE - NEUTRAL

BROWN - LIVE

YELLOW/GREEN STRIPE - EARTH

HOBBY PLUS SPRAY GUN




Position No	Description	Part No
1	Needle	GP123
2	Needle Spring	GP124
3	Paint Flow Adjusting Screw	GP125
4	Gun Body - Spraymate	GP126
5	Gun Body - Spraymaster	GP127
6	Cruciform	GP128
7	Spray Jet	GP129
8	Aircap	GP130
9	Aircap Locking Ring	GP131
10	Paint Tube	GP132
11	Cup Top Seal	GP133
12	Paint Cup	GP134
13	Gland Seal (4)	GP135
14	Gland Nut	GP136
15	Trigger	GP137
16	Trigger Pin	GP138
17	Jet Seal	GP139

USING THE HOBBY PLUS SPRAY GUN


SPRAY PATTERN

The shape of spray pattern can be determined by rotating the aircap into 3 positions. To select the spray pattern required, slightly slacken the aircap locking ring, turn the aircap to one of the positions shown below, then tighten the aircap locking ring - finger tight only.



- 1 Use this position when spraying from side to side
- 2 Use this position when spraying up and down
- 3 Use this position when spraying small items, corners or angles

PAINT FLOW




Paint flow adjusting screw

The amount of paint being applied is adjusted with the paint flow adjusting screw. Turn in to decrease the flow and turn out to increase the flow.


USING THE ANB300 SPRAY GUN

SPRAY PATTERN / SHAPE ADJUSTMENT


The shape of spray pattern can be determined in three ways, turn the air cap to one of the positions shown below, you may need to loosen the air cap retaining ring first.




For spraying side to side



For spraying up and down




Use the control knob to change from the fan to spot pattern
quarter turn only required



When spraying upwards (ceilings) turn the cup top 180° so that the paint tube faces towards the handle


PAIN T FLOW ADJUSTMENT




Turn the paint flow adjusting screw in to decrease the flow and screw out to increase the flow.

Hint ! It is better to spray two light coats rather than one heavy coat, this will reduce the risk of runs or sagging forming.

AIR HOSE CONNECTION




The air hose is fitted with a quick release connector, pull back the collar of the connector then push on to the base of the spray gun handle, at the same time release the collar. To remove, pull back the collar and the connector will come away from the spray gun.



To connect the air hose to the turbine, screw the hose connector onto the outlet of the turbine making sure the thread is not crossed.

It is normal for this hole to exhaust air when the machine is in use.



To use the spraygun holder pull back on the collar of the connector and push the spraygun into the base of the connector, release the collar to hold the gun in place.

SELECTING A SPRAY SET UP

The ANB300 Spray gun is factory fitted with a 1.3mm Needle, Jet and Air Cap set.

Part No	Size	Material
ANB329	0.8mm	Lacquers, Wood Stains, Synthetics, Cellulose, Acrylics, Oil, Fine intricate output.
ANB330	1.3mm	Lacquers, Wood Stains, Synthetics, Cellulose, Acrylics, Oil, Polyurethanes, Glitter Paints, Fluorescents, Creosote, Wood Primer. Fine to Medium output.
ANB331	2.0mm	Polyurethanes, Glitter Paints, Fluorescents, Creosote, Wood Primer, Emulsions, Adhesives, Floor/Paving Paint, Medium to Heavy output.
ANB336	2.8mm	Hammers, Oil Base, Primers, Enamels, Marine, Masonry, Texture Coatings, Heavy Primers, Water and Solvent based Adhesives. Higher viscosity products.

CLEANING THE GUN AFTER USE

Care must be taken in cleaning and maintaining your spray gun.

- 1, Empty any unused material from the paint cup and wash out any residue with the appropriate solvent.
- 2, Remove air cap, Clean with solvent. Ensure the air holes in the cap are clear.
- 3, To clean the spray jet you will have to first remove the air cap.

Ensure all parts are clean before re-assembly.

Note:- Replace any worn or damaged seals.

FAULT FINDINGS

Paint leaking from the spray jet.

Needle not seating in the spray jet

Check for debris or worn parts

Poor atomisation / splattering

Paint too thick

Check viscosity

Wrong spray set up

Refer to guide

Paint leaking


From gland nut/seal

Check the tightness of the nut or replace seal

From cup

Check cup seal

ANB300 SPRAY GUN




1	ANB301	Air Cap Retaining Ring	18	ANB317	Air Feed Connector
2	ANB330	Air Cap 1.3mm	19	ANB318	Gland Screw
3	ANB330	Spray Jet 1.3mm	20	ANB319	Gland
4	ANB302	Air Distributor	21	ANB320	Fluid Stem
5	ANB304	Spray Gun Body	22	ANB321	Trigger Pivot
6	ANB305	Set Pin	23	ANB322	Circlip
7	ANB306	Air Flow Control Stem	24	ANB323	Trigger
8	ANB307	O Ring	25	ANB324	Handle
9	ANB308	O Ring	26	ANB325	Air Tube
10	ANB309	Control Valve	27	ANB326	Connector
11	ANB310	Control Knob	28	ANB327	Needle Spring
12	ANB311	Paint Flow Adjusting Body	29	ANB328	Paint Flow Adjusting Screw
13	ANB312	O Ring	30	ANB330	Needle 1.3mm
14	ANB313	Seal	31	APGA237	Air Feed Pipe
15	ANB314	Valve Spring	32	ANB333	Cup Top
16	ANB315	Air Valve	33	ANB334	Cup Top Seal
17	ANB316	Valve Seal	34	ANB335	Paint Cup
			35	ANB337	Air Flow Control Assembly

PAINT VISCOSITY

The correct viscosity of the material is essential to ensure an optimum finish. Most materials will require thinning before use.

To achieve the correct viscosity you need to use the viscosity cup supplied. Hold your finger over the small hole on the base of the cup, fill the cup with the material to be sprayed. Take away your finger and time the material until it ceases to be a steady flow and starts to drip.



The following chart may be helpful.



VISCOSITY CHART	
Type of product	Approximate time
Cellulose	18 seconds
Creosote	As supplied
Emulsion	27 seconds
Hammer	24 seconds
Gloss Enamel	24 seconds
Polyurethane (Household. 1 pack)	24 seconds
Polyurethane (Industrial. 2 pack)	As Instructed
Wood Stain	As supplied
Adhesives	17 seconds
Gel Coats	18 seconds

SPRAYING TECHNIQUES

Before commencing to spray it is advisable to spray on to a sheet of card or suitable material to ensure the spray pattern and viscosity are correct.


Hold the spray gun approximately 150 to 200mm from the work to be sprayed. If the spray gun is held too close to the work piece then excessive material will be deposited, If it is held too far away then a dry spray is caused giving a rough sandy finish to the work.

At the beginning of each stroke trigger the spray gun on and at the end of each stroke trigger off, this will avoid a build up of material at the beginning and ends of each stroke. The speed of stroke should be constant. Move the spray gun parallel to the work surface, tilting the spray gun up or down or in a curve will give an uneven coat.



SPRAYING LARGE SURFACES


Adjust the paint flow to increase the flow of material, spray in sections overlap each stroke by approximately 30%.



SPRAYING CORNERS


Adjust the spray pattern to the spot, decrease the material flow and spray both surfaces at the same time.

Always spray the edges and corners before the main work.




SPRAYING CYLINDERS

For small diameter cylinders up to 30cm spray vertically, for larger cylinders spray around the cylinder in sections as you would on large surfaces.




FILTER REMOVAL / REPLACEMENT


IMPORTANT NOTES: ALWAYS TURN THE TURBINE OFF AND REMOVE THE MAINS PLUG BEFORE CARRYING OUT ANY SERVICE WORK.




Remove all 4 fixings




Remove 2 fixings / washers



Remove filter plates from both sides of the turbine



Remove both filter elements



Replace the filter elements and re-assemble in reverse order.

The part number for the filter element is APT622. Remember these should be replaced every 6 months or sooner in dusty environments.

FAULT FINDING

Sags or runs:

Too much material
Spray gun moved too slowly
Material too thin
Spray overlapped too much

Screw in the paint flow adjuster
Move the spray gun faster
Check viscosity
Only overlap by 30%

Dusty Appearance:

Not enough material
Spray gun too far away from work
Surface not prepared

Unscrew paint flow adjuster
Hold spray gun 150 - 200mm from work
Prepare surface, ensure dust free

PREVENTATIVE MAINTENANCE

Your Apollo turbine requires minimal maintenance, Check the turbine filters every time you use the turbine, replace the filters every 6 months or sooner in dusty environments.

The turbine bearings are sealed and lubricated for life. There is no maintenance or adjustment required.

Replace all spray gun gaskets and seals at regular intervals to prevent leakages.

If you require any further assistance please call your local dealer or:-

Bambi Air Limited
152 Thimble Mill Lane
Heartlands
Birmingham
B7 5HT
United Kingdom

Tel: 44 (0) 121 322 2299

Fax: 44 (0) 121 322 2297

E. Mail: sales@bambi-air.co.uk

NOTES

BAMBI AIR LTD

152 Thimble Mill Lane, Heartlands, Birmingham, West Midlands B7 5HT
Tel: 0121 322 2299, Fax: 0121 322 2297, Email: sales@bambi-air.co.uk



EC Declaration of Conformity - Declaration de Conformite CE
EG Konformitätserklärung
Declaracion de Conformidad CE - EG Verklaring van Overeenstemming

Bambi Air Ltd declares that this product conforms to the European Directives listed below.

Bambi Air Ltd declare que ce produit est conforme aux directives europeennes enumerees ci-dessous.

Bambi Air Ltd declara que este producto cumple con la Directiva Europea listada abajo.

Bambi Ai Ltd verklaart dat dit product voldoet aan de onderstaande Europese Richtlijnen

Bambi Air Ltd erklart hiermit, dass dieses Produkt mit den Bestimmungen der Nachstehenden EU-Richtlinien übereinstimmt.

Machinery Safety Standard 89/392 EC, Low Voltage Directive 2006/95
EC Machinery Directive 2006/42 EC, Electromagnetic Compatibility
2004/108 EC
EN60034, EN60204-1:2007, EN ISO12100-1-2:2005, EN
ISO13857:2010
CE Marking applied for the first time in 1997

AFFIX SERIAL NUMBER
LABEL HERE

A handwritten signature in black ink, appearing to read 'L Clutterbuck'.

L Clutterbuck
Director